



Certificate No: EW506C



This certificate is valid for Building Regulations & associated technical guidance in force on the date of registration and for the regulations in the countries indicated

Permavent MAX – All Zones

Description of Product

Permavent MAX – All Zones 150g is a high performance breathable membrane used on all types of domestic and commercial roofing and walling applications.

Please consult the 'Conditions of Certificate' and 'Non-Regulatory Information' sections to see if the product is acceptable for use on sites covered by LABC Warranty.



Key Factors Assessed

- ☐ Mechanical Resistance & Stability
- ☐ Health, Hygiene and Environmental
- ☐ Safety in Use
- ☐ Durability serviceability and identification

Validity

This certificate was first issued on 23rd April 2015 and is valid until 23rd October 2021

Issue Dated 4th March 2021

Scope of Registration

Permavent use the very latest technology from the medical industry to encapsulate the highest grade hydrophobic film inside the very highest quality spunbond polypropylene layers. Permavent membranes are manufactured in a single process that greatly improves the quality and integrity of our membranes. This 3 in 1 process means that Permavent offer superior strength, breathability, flexibility and durability.

Permavent MAX – All Zones has been tested and certified by independent European laboratories and manufactured under the strictest ISO requirements to permit CE marking under CEN EN 13859:1 2010.

Conditions of Certificate

Must be stored, handled and installed in accordance with the BBA Certificates, IAB Certification, any stipulated requirement within the BRE Wind Driven Test report and manufacturer's instructions.

Condensation risk assessment calculations in accordance with BS 5250: 2011 should be carried out for specific applications. When using thermal insulation with a low vapour resistance, a vapour control layer on the warm side of the insulation may be required. Where the roof may be subject to high humidity conditions (eg kitchens, swimming pools, bathrooms) a vapour control layer should be considered with all types of insulation.

Should not be exposed to direct sunlight for long periods.

LABC consider that, Permavent MAX – All Zones, will meet the functional requirements of the Building Regulations (listed below) if the criteria detailed in this certificate are met;



The Building Regulations 2010 (as amended) England & Wales

AD C Site preparation and resistance to contaminants and moisture

Note: The product is acceptable subject to conditions.

Regulation 7 Materials and Workmanship

Note: Are appropriate for the circumstances in which they are used, subject to conditions.



The Building Regulations 2010 (as amended) England

None presently



The Building Regulations 2010 (as amended) Wales

None presently



The Building (Scotland) Regulations 2004 (as amended)

If you would like to discuss a specific use of the product in Scotland it will require an additional assessment under the Scottish Building Regulations and accordingly you should contact the LABSS STAS Administrator at www.labss.org

Non-Regulatory Information



LABC Warranty

The product has not been assessed by LABC Warranty.

Supporting Documentation

BRE Report No P111709-1000 Issue 3 Dated 25th July 2018

Declaration of Performance Document No PVB/MAX/001 Dated 8th May 2018

Permavent Max All Zones Fitting Instructions

Permavent Max All Zones Product Card

Contact Information

Permavent Limited
11 Cumberland Drive
Weymouth
Dorset
DT4 9TB
Tel: 01305 766703
Email: post@permavent.co.uk
Website: www.permavent.co.uk