

Declaration of Performance

Document number: PVB/MAX/001

Product Identification: Permavent MAX | ALL ZONES, 150g/m²

Intended Use of the Product: Watertightness, vapour permeable membrane – underlay for discontinuous roofing.
(The product must be installed in accordance with manufacturer's instructions.)

Manufacturer: XXXXXXXXXXXXXXXXXXXX*

Authorised Representative: Permavent Ltd. 11 Cumberland Drive, Granby Industrial Estate, Weymouth Dorset. DT4 9TB

System of AVCP: System 3

Notified Body: No. 1434
Polskie Centrum Badań i Certyfikacji S.A. (PCBIC) –
Laboratorium Materiałów Budowlanych w Gdańsku

Harmonised Standards: EN 13859-1:2010 “Flexible products for Watertightness. Definitions and characteristics of underlays- Part 1: Underlays for discontinuous roofing”

Declared Performance:

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class: E	13859-1:2010
Resistance to water penetration	Class: W1	
Maximum tensile strength - along	350 N/50mm [$\pm 30\%$]	
Maximum tensile strength - across	240 N/50mm [$\pm 30\%$]	
Elongation - along	70% [$\pm 20\%$]	
Elongation - across	70% [$\pm 30\%$]	
Resistance to tearing (nail shank) - along	140 N [$\pm 15\%$]	
Resistance to tearing (nail shank) - across	230 N [$\pm 20\%$]	
Flexibility at low temperature	-40°C	13859-1:2010
Technical Parameters		

Mass per unit area	150 g/m ² [±5%]
Water vapour transmission properties	0,02 Sd [m]

The performance of the product identified above is in conformity with the set of declared performances. This declaration is issued in accordance with Regulation (EU) No 305/2011. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of: Permavent Ltd.
Place of issue: Weymouth, UK.
Date of issue: 12.07.18
Name: Timofei Yeremeyev
Position: Director
Signature: 