


Declaration of Performance

Permavent Apex Air Permeable Membrane

Product identification description	Permavent Apex Air & Vapour Permeable Roofing Underlay	
Product identification as a construction product	Identified by brand colour serial number and batch traceability	
Manufacturer	Permavent Limited. 11 Cumberland Drive, Granby Industrial Estate, Weymouth, Dorset. DT4 9TB	
Authorised representative	Timofei Yeremeyev 12 Lierweg Born/Amel 4770 Belgium	
System of AVCP	System 3	
Notified testing body No. 0799	Kiwa GmbH Niederlassung TBU Gutenbergstraße 29 48268 Greven	
Essential Characteristics	Performance	Standard
Reaction to fire	Class E	EN 13501
Resistance to water Penetration	Class W1	EN 13859-1
Tensile strength MD	358 N/50mm BS EN 12311-1	EN 13859-1
Tensile strength CD	304 N/50mm BS EN 12311-1	EN 13859-1
Flexibility at low temperature	- 40 °C	EN 13859-1
Water vapour transmission	0.01 Sd	EN 12572
1. Air permeability	2. >36.72m ³ /m ² .h50pa	3. EN 12114
Resistance to nail tearing MD	214 N BS EN 12310-1	EN13859-1
Resistance to nail tearing CD	218N BS EN 12310-1	EN13859-1
Mass per unit area	180 g/m ²	

We confirm that the product conforms, having been tested to the construction products regulation and as the manufacturer accept responsibility for the compliance of the product.

Signed on behalf of the manufacturer:



Timofei Yeremeyev
Director
Permavent Ltd
January 2024