

Declaration of Performance

Permavent Eco Vapour Permeable Membrane

Product identification description	Permavent Eco Vapour Permeable Roofing Underlay	
Product identification as a construction product	Identified by brand colour serial number and batch traceability	
Manufacturer	Permavent Limited. 11 Cumberland Drive, Granby Industrial Estate, Weymouth, Dorset. DT4 9TB	
Authorised representative	Timofei Yeremeyev 12 Lierweg Born/Amel 4770 Belgium	
System of AVCP	System 3	
Notified testing body No.1434	Polskie Centrum Badań i Certyfikacji S.A. (PCBIC) – Laboratorium Materiałów Budowlanych w Gdańsku	
Essential Characteristics	Performance	Standard
Reaction to fire	Class E	EN 13501
Resistance to water penetration	Class W1	EN 13859-1
Tensile strength MD	260 N/50mm BS EN 12311-1	EN 13859-1
Tensile strength CD	170 N/50mm BS EN 12311-1	EN 13859-1
Flexibility at low temperature	- 40 °C	EN 13859-1
Water vapour transmission	0.02 Sd	EN 12572
Resistance to nail tearing MD	100 N BS EN 12310-1	EN13859-1
Resistance to nail tearing CD	120 N BS EN 12310-1	EN13859-1
Mass per unit area	90 g/m ²	

We confirm that the product conforms, having been tested to the construction products regulation and as the manufacturer accept responsibility for the compliance of the product.

Signed for on behalf of the manufacturer:

Timofei Yeremeyev

Director
Permavent Ltd
January 2024