



## Declaration of Performance

### Permavent Safeshield INT Reflect Fire Safe A Rated Membrane

Product identification description	Permavent Safeshield INT Reflect Fire Safe A Rated Membrane	
Product identification as a construction product	Identified by brand colour serial number and batch traceability	
Manufacturer	Permavent Limited, 11 Cumberland Drive, Granby Industrial Estate, Weymouth, Dorset. DT4 9TB	
Authorised representative	Timofei Yeremeyev 12 Lierweg Born/Amel 4770 Belgium	
System of AVCP	System 3 – BS EN 13859-1 Flexible sheets for waterproofing	
Notified testing body No. 1301	Technicky a skusobny ustav stavebny, n. o Studena 3 82104 BRATISLAVA	 TECHNICKÝ A SKÚŠOBNÝ ÚSTAV STAVEBNÝ BUILDING TESTING AND RESEARCH INSTITUTE
Essential Characteristics	Performance	Designated Standard
Reaction to fire	Class A2-s1,d0	EN 13501
Resistance to water penetration	Class W2	EN 13859-1
Tensile Strength MD	1362 N/50mm BS EN 12311-1	EN 13859-1
Tensile Strength CD	1349 N/50mm BS EN 12311-1	EN 13859-1
Flexibility at low temperature	- 40 °C	EN 13859-1
Water vapour transmission	>2,500sd	EN 12572
Resistance to Nail Tearing MD	150 N BS EN 12310-1	EN 13859-1
Resistance to Nail Tearing CD	150 N BS EN 12310-1	EN 13859-1
Resistance to UV Exposure	9 months 5,000 hours tested	
Airtightness	0.093m <sup>3</sup> / (h x m <sup>2</sup> x 50 pa)	EN 12114
Mass per unit area	140 g/m <sup>2</sup>	

We confirm that the product conforms, having been tested, to the construction products regulation and as the manufacturer accepts responsibility for the compliance of the product.

Signed for on behalf of the manufacturer:



**Timofei Yeremeyev**  
Director  
Permavent Ltd  
January 2024