

UNIVERSAL LOW PITCH ROOF VENT

FOR SLATES WITH EASY SLATE

FITTING GUIDE

FEATURES AND BENEFITS

- ✓ Universal vent for low pitch slate roof.
- ✓ Roof pitch as low as 12.5°.
- ✓ Suits all sizes of natural and fibre cement slates.
- ✓ Suitable for SVP, extraction fans and roof ventilation.
- ✓ In-built adapter 100mm, 125mm and oval adapter.
- ✓ Airflow up to 12,750 mm² when used with the 125mm round spigot connector.
- ✓ Part of the Easy Roof System 40 year guarantee.

INSTALLATION GUIDANCE

- ✓ Determine the position of the Universal Vent and cut an envelope 180mm wide and 140mm long in the underlay as shown in Fig 1 and Fig 2. Fold back the underlay (Fig 2). Battens may need to be cut to create the space.
- ✓ Install the slates with the Easy Slate system around the envelope cut in the underlay as shown in Fig 3. Slates need to be clean, dry and dust free.
- ✓ Position and align the vent so it is central over the hole in the slates pulling it forward so the front tab on the base rests against the slates below (Fig 4).
- ✓ Remove the backing film from the flashing skirt and lower the vent into position. Dress the flashing down on the adjacent slates working from the inside out contouring into the lap of the slates (Fig 5).
- ✓ Then dress down the flashing onto the course of slate below and above (Fig 6).
- ✓ Finish installing the slates with the Easy Slate System and slate around the vent as per normal to create a weathertight seal (Fig 7).

STORAGE

Permavent Universal Low Pitch Vent should be stored in an upright position, in a well ventilated space that is under cover and is free from moisture. Permavent Universal Low Pitch Vent should not be stored in direct sunlight and prolonged UV exposure may affect the performance of this product.

KIT CONTENTS

1 unit per box

SUITABLE FOR PLAIN TILES AND SLATES

BS5250: 2021 AND BS5534: 2014 +A2 2018 COMPLIANT



Fig 1.



Fig 2.



Fig 3.



Fig 4.



Fig 5.



Fig 6.




Fig 7.

CONTACT INFORMATION

For product, technical and sales support please contact Permavent on:

Tel: (+44) 1305 766 703.

Email: enquiries@permavent.co.uk.

Please scan this QR code to find the contact information for your regional Permavent Representative.



PERMAVENT

PERMAVENT.CO.UK

11 Cumberland Drive, Granby Industrial Estate, Weymouth, DT4 9TB.

UNIVERSAL LOW PITCH ROOF VENT

FOR PLAIN TILES WITH PLAIN EASY FITTING GUIDE

FEATURES AND BENEFITS

- ✓ Universal vent for low pitch plain tile roof.
- ✓ Roof pitch as low as 17.5°.
- ✓ Suits for concrete and clay plain tiles.
- ✓ Suitable for SVP, extraction fans and roof ventilation.
- ✓ In-built adapter 100mm, 125mm and oval adapter.
- ✓ Airflow up to 12,750 mm² when used with the 125mm round spigot connector.
- ✓ Part of the Easy Roof System 40 year guarantee.

INSTALLATION GUIDANCE

- ✓ Determine the position of the Universal Vent and cut an envelope 180mm wide and 140mm long in the underlay as shown in Fig 1 and Fig 2. Fold back the underlay (Fig 2). Battens may need to be cut to create the space.
- ✓ Install the plain tiles with the Plain Easy system around the envelope cut underlay as shown in Fig 3 and Fig 4. Tiles need to be clean, dry and dust free.
- ✓ Position and align the vent so it is central over the hole in the plain tiles pulling it forward so the front tab on the base rest against the plain tiles below.
- ✓ Remove the backing film from the flashing skirt and lower the vent into position. Dress the flashing down on the adjacent plain tiles working from the inside out contouring into the lap of the plain tiles (Fig 5).
- ✓ Then dress down the flashing onto the course of plain tiles below and above (Fig 6).
- ✓ Finish installing the plain tiles with the Plain Easy system and tile around the vent as per normal to create a weathertight seal (Fig 7).

STORAGE

Permavent Universal Low Pitch Vent should be stored in an upright position, in a well ventilated space that is under cover and is free from moisture. Permavent Universal Low Pitch Vent should not be stored in direct sunlight and prolonged UV exposure may affect the performance of this product.

KIT CONTENTS

1 unit per box

SUITABLE FOR PLAIN TILES AND SLATES

BS5250: 2021 AND BS5534: 2014 +A2 2018 COMPLIANT




Fig 1.



Fig 2.



Fig 3.



Fig 4.



Fig 5.



Fig 6.



Fig 7.

CONTACT INFORMATION

For product, technical and sales support please contact Permavent on:

Tel: (+44) 1305 766 703.

Email: enquiries@permavent.co.uk.

Please scan this QR code to find the contact information for your regional Permavent Representative.



PERMAVENT

PERMAVENT.CO.UK

11 Cumberland Drive, Granby Industrial Estate, Weymouth, DT4 9TB.